



17 Shepard Street • Lawrence, MA 01843 USA

+1.978.683.9411

www.keypolymer.com

Issuing Date 04-Sep-2015

Revision Date 14-Jul-2017

Revision Number 5

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product identifier

Product Name KEY PC2021A

Other means of identification

Product Code(s) PC2021A

Product Technology Epoxy A side

Document Tough-Seal 21A

None

Epoxy A side. FOR INDUSTRIAL USE ONLY.

Restrictions on use: Do not use this product for any use other than intended

Manufacturer Address

Key Polymer Corporation
17 Shepard Street
Lawrence, MA 01843, USA

Company Phone Number 978-683-9411 (8AM - 5PM EST) (M-F)

Emergency Telephone Chemtrec 1-800-424-9300 (24 Hours)

Chemtrec International Phone +1 703 527-3887

2. Hazards Identification

Classification

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS). This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 2
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1 (thymus)
Specific target organ toxicity (repeated exposure)	Category 1 (thymus)

Emergency Overview

DANGER

Hazard statements

Causes skin irritation

Causes serious eye irritation
 May cause an allergic skin reaction
 Suspected of causing genetic defects
 May cause cancer
 May damage fertility or the unborn child
 Causes damage to organs
 (thymus)
 Causes damage to organs through prolonged or repeated exposure
 (thymus)



Appearance Viscous White

Physical state Liquid

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Use personal protective equipment as required
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing should not be allowed out of the workplace
 Do not breathe dust, fumes, or vapors
 Do not eat, drink or smoke when using this product
 Wear protective gloves, protective clothing, eye protection, face protection

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention
 IF ON SKIN: Wash with plenty of soap and water
 Take off contaminated clothing and wash before reuse
 If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up
 Please see Product Information Bulletin (PIB) for shelf life and storage information.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/regional/international regulations

Hazards Not Otherwise Classified (HNOC)

Other Information

May be harmful if swallowed, Toxic to aquatic life with long lasting effects
 98.3665% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

Chemical Family
Chemical nature

Epoxy A Side
 Epoxy resin mixture.

Chemical name	CAS No.	Weight-%	Trade secret
Bisphenol A diglycidyl ether resin	25068-38-6	50 - 85	*
Calcium carbonate	1317-65-3	15 - 30	*
Proprietary epoxy resin	Proprietary	1 - 5	*
Dibutyltin oxide	818-08-6	1 - 3	*
Silicon dioxide	14808-60-7	0.1 - 0.3	*

Calcium carbonate, when encapsulated in a polymer, is not expected to pose a respirable health hazard when processed under normal conditions of use.

* The exact percentage (concentration) of composition may have been withheld as a trade secret.

4. First Aid Measures

Description of first aid measures

General advice	Use first aid treatment according to the nature of the injury. For further assistance, contact your local Poison Control Center. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists: Get medical advice/attention.
Skin contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
Ingestion	Not an expected route of exposure. If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.
Self-protection of the first aider	First Aider: Pay attention to self-protection. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-Fighting Measures

Suitable Extinguishing Media

Use CO₂, dry chemical, or foam

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water ways. Dike for water control.

Hazardous combustion products

Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See Section 10 Hazardous Decomposition Products for additional information.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ventilate affected area. Extremely slippery when spilled.

Other Information Use personal protective equipment as required.

For Emergency Responders Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information. Do not allow into any sewer, on the ground or into any body of water.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store and handle away from heat, flames and oxidizing materials. Please see Product Information Bulletin (PIB) for shelf life and storage information.

Incompatible materials Strong oxidizing agents. Strong acids. Strong bases.

8. Exposure Controls/Personal Protection

Control parameters

Exposure Limits The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium carbonate 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Dibutyltin oxide 818-08-6	STEL: 0.2 mg/m ³ Sn TWA: 0.1 mg/m ³ Sn S*	TWA: 0.1 mg/m ³ Sn (vacated) TWA: 0.1 mg/m ³ Sn (vacated) S*	IDLH: 25 mg/m ³ Sn TWA: 0.1 mg/m ³ except Cyhexatin Sn
Silicon dioxide 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust

		: (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	
--	--	---	--

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems
-----------------------------	--

Individual protection measures, such as personal protective equipment

Eye/face protection	Splash Goggles.
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties
--

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Mild
Appearance	Viscous	Odor threshold	N/A
Color	White		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	N/A	
Melting point / freezing point	0 °C	
Boiling point / boiling range	> 200 °C	
Flash point	> 180 °C	CC (closed cup)
Evaporation rate	N/A	
Flammability (solid, gas)	N/A	
Flammability Limit in Air		
Upper flammability limit:	N/A	
Lower flammability limit:	N/A	
Vapor pressure	N/A	
Vapor density	N/A	
Relative density	1.33	
Water solubility	Negligible	
Solubility in other solvents	N/A	
Partition coefficient	N/A	
Autoignition temperature	N/A	
Decomposition temperature	N/A	
Kinematic viscosity	5640 cSt	
Dynamic viscosity	7500 cps @ 25° C	
Explosive properties	N/A	
Oxidizing properties	N/A	

Other Information

Softening point	N/A
Molecular weight	N/A
VOC Content (%)	N/A
Liquid Density	11.1 pounds/gallon
Bulk density	N/A

10. Stability and Reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

Hazardous polymerization None under normal processing.

Conditions to avoid

Keep out of reach of children. Extremes of temperature and direct sunlight. Mixture with or exposure to incompatible materials.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition products

Carbon monoxide. Carbon Dioxide (CO₂). Aldehydes. Aromatic hydrocarbons. May emit toxic fumes under fire conditions.

11. Toxicological Information

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation Remove to fresh air.

Eye contact Vapor may cause irritation. Avoid contact with eyes. Severely irritating to eyes.

Skin contact Avoid contact with skin. Irritating to skin. May cause sensitization by skin contact.

Ingestion Not an expected route of exposure. May be harmful if swallowed.

Chemical name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Bisphenol A diglycidyl ether resin 25068-38-6	= 11400 mg/kg (Rat)	-	-
Proprietary epoxy resin	= 17100 mg/kg (Rat)	> 3987 mg/kg (Rabbit)	-
Dibutyltin oxide 818-08-6	= 164 mg/kg (Rat)	-	-

Information on toxicological effects

N/A.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Irritating to skin.

Serious eye damage/eye irritation Irritating to eyes.

Irritation Irritating to eyes and skin.

Sensitization May cause sensitization by skin contact.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity Silicon Dioxide (CAS 14808-60-7) is a naturally occurring substance that poses low respirable carcinogen risk when encapsulated in a polymeric liquid. If sanding or grinding finished product, wear appropriate personal protective equipment for respirable dust hazards.

Chemical name	ACGIH	IARC	NTP	OSHA
Silicon dioxide	A2	Group 1	Known	X

14808-60-7				
ACGIH (American Conference of Governmental Industrial Hygienists) A2 - Suspected Human Carcinogen IARC (International Agency for Research on Cancer) Group 1 - Carcinogenic to Humans NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present				
Reproductive toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard.			
Developmental toxicity	May cause harm to the unborn child.			
Teratogenicity	May cause harm to the unborn child.			
STOT - single exposure	thymus.			
STOT - repeated exposure	thymus.			
Chronic Toxicity	Prolonged exposure may cause chronic effects. Repeated skin contact may lead to irritation and to sensitization, possible with cross-sensitization to other epoxies. Possible risk of irreversible effects.			
Aspiration hazard	N/A.			

Numerical measures of toxicity - Product Information

Unknown acute toxicity	98.3665% of the mixture consists of ingredient(s) of unknown toxicity
The following values are calculated based on chapter 3.1 of the GHS document	
ATEmix (oral)	3,368.00 mg/kg
ATEmix (dermal)	5,439.72 mg/kg

12. Ecological Information

Ecotoxicity

Toxic to aquatic life with long lasting effects

31.735 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Dibutyltin oxide 818-08-6		0.8: 48 h Oryzias latipes mg/L LC50	

Persistence and degradability

N/A

Other adverse effects

N/A

13. Disposal Considerations

Waste treatment methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.

Chemical name	California Hazardous Waste Status
Dibutyltin oxide 818-08-6	Toxic

14. Transport Information

Note: A197 - Not restricted provided that the net quantity in any receptacle does not exceed 5 Kg or 5 L and the packaging meets defined standards.

DOT Not regulated

ICAO (air)

UN/ID no.	UN3082
Proper shipping name	Environmentally hazardous Substance N.O.S. (Bisphenol A epoxy resin)
Hazard Class	9
Packing Group	III

IATA

UN/ID no.	UN3082
Hazard Class	9
Packing Group	III

IMDG

UN/ID no.	UN3082
Proper shipping name	Environmentally Hazardous Substance Liquid N.O.S. (Bisphenol A epoxy resin)
Hazard Class	9
Packing Group	III
Special Provisions	IMDG code 2.9.3
Marine pollutant	This product contains a chemical which is listed as a severe marine pollutant according to IMDG/IMO

15. Regulatory Information

International Inventories

TSCA All components of this product are either exempt or included on the TSCA Inventory in compliance with the Toxic Substances Control Act.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

The following chemicals may be contained in this product in de minimis amounts not required for listing in section 3. However,

these chemicals do appear on some state Right-to-Know (RTK) and/or other hazardous substance lists. Please check your state's listings for more information.

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Dinonyl phthalate - 28553-12-0	Carcinogen
Silicon dioxide - 14808-60-7	Carcinogen
Glycidyl phenyl ether - 122-60-1	Carcinogen Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Calcium carbonate 1317-65-3	X	X	X
Silicon dioxide 14808-60-7	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other Information

NFPA	Health hazards 2	Flammability 1	Instability 0	Physical and chemical properties -
HMIS	Health hazards 2*	Flammability 1	Physical hazards 0	Personal Protection X
<i>Chronic Hazard Star Legend</i>		<i>* = Chronic Health Hazard</i>		

Prepared By Key Polymer Corp Compliance
Issuing Date 04-Sep-2015
Revision Date 14-Jul-2017

Revision Note

N/A

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet