

SAFETY DATA SHEET



17 Shepard Street • Lawrence, MA 01843 USA +1.978.683.9411

www.keypolymer.com

Issuing Date 12-Jan-2015 Revision Date 20-Apr-2016 Revision Number 8

1. Identification of the Substance/Preparation and of the Company/Undertaking

Product identifier

Product Name KEY PC2032A

Other means of identification

Product Code(s)
Product Technology
Document
PC2032A
Epoxy A side
Tough-Seal 32A

None

Epoxy A side. FOR INDUSTRIAL USE ONLY.

Restrictions on use: Do not use this product for any use other than intended

Manufacturer Address Key Polymer Corporation 17 Shepard Street Lawrence, MA 01843, USA

Company Phone Number 978-683-9411 (8AM - 5PM EST) (M-F) Emergency Telephone Chemtrec 1-800-424-9300 (24 Hours)

Chemtrec International Phone +1 703 527-3887

2. Hazards Identification

Classification

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS). This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

Emergency Overview

DANGER			
Hazard statements	i		
Harmful if inhaled			

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Suspected of causing genetic defects

May damage fertility or the unborn child

Causes damage to organs

(thymus)

Causes damage to organs through prolonged or repeated exposure

(thymus)



Appearance Opaque White

Physical state Liquid

Odor None

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing should not be allowed out of the workplace

Do not breathe dust, fumes, or vapors

Do not eat, drink or smoke when using this product

Wear protective gloves, protective clothing, eye protection, face protection

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

Take off contaminated clothing and wash before reuse

If skin irritation or rash occurs: Get medical advice/attention

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store locked up

Please see Product Information Bulletin (PIB) for shelf life and storage information.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/regional/international regulations

Hazards Not Otherwise Classified (HNOC)

Other Information

May be harmful if swallowed, Toxic to aquatic life with long lasting effects

4.5% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients

Substance

Chemical Family Epoxy A Side

Chemical nature

Epoxy resin mixture.

Chemical name	CAS No.	Weight-%	Trade secret
Bisphenol A diglycidyl ether resin	25068-38-6	75 - 95	*
Proprietary epoxy resin	Proprietary	1 - 5	*
Dibutyltin dilaurate	77-58-7	1.3	*

^{*} The exact percentage (concentration) of composition may have been withheld as a trade secret.

4. First Aid Measures

Description of first aid measures

General advice Use first aid treatment according to the nature of the injury. For further assistance, contact

your local Poison Control Center. In case of accident or unwellness, seek medical advice

immediately (show directions for use or safety data sheet if possible).

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

eye irritation persists: Get medical advice/attention.

Skin contact Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if

irritation develops and persists.

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Ingestion Not an expected route of exposure. If swallowed, do not induce vomiting: seek medical

advice immediately and show this container or label.

Self-protection of the first aider First Aider: Pay attention to self-protection. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-Fighting Measures

Suitable Extinguishing Media

Use CO2, dry chemical, or foam.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or water ways. Dike for water control.

Hazardous combustion products

Irritating or toxic substances may be emitted upon burning, combustion or decomposition. See Section 10 Hazardous Decomposition Products for additional information.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full

protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ventilate affected area. Extremely slippery when spilled.

Other Information Use personal protective equipment as required.

For Emergency Responders

Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information. Do not allow into any sewer, on the

ground or into any body of water.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and Storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store and handle

away from heat, flames and oxidizing materials.

Incompatible materials Strong oxidizing agents, Strong acids, Strong bases.

8. Exposure Controls/Personal Protection

Control parameters

Exposure Limits This product, as supplied, does not contain any hazardous materials with occupational

exposure limits established by the region specific regulatory bodies

	Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Γ	Dibutyltin dilaurate	STEL: 0.2 mg/m ³ Sn	TWA: 0.1 mg/m³ Sn	IDLH: 25 mg/m³ Sn
1	77-58-7	TWA: 0.1 mg/m³ Sn	(vacated) TWA: 0.1 mg/m ³ Sn	TWA: 0.1 mg/m ³ except
1		S*	(vacated) S*	Cyhexatin Sn

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Splash Goggles.

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

N/A

Physical state Liquid
Appearance Opaque
Color White

Odor None Odor threshold N/A

Remarks • Method

Property Values N/A

pH N/A
Melting point / freezing point N/A
Boiling point / boiling range > 200 °C
Flash point > 203 °C
Evaporation rate N/A

3 °C Setaflash Closed Tester

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit: N/A Lower flammability limit: N/A Vapor pressure N/A Vapor density N/A Relative density 1.15 Water solubility Negligible Solubility in other solvents N/A Partition coefficient N/A **Autoignition temperature** N/A

Partition coefficient N/A
Autoignition temperature N/A
Decomposition temperature N/A
Kinematic viscosity N/A
Dynamic viscosity N/A

Evaluation proportion N/A

Explosive properties Not an explosive

Oxidizing properties N/A

Other Information

Softening point N/A
Molecular weight N/A
VOC Content (%) N/A

Liquid Density 9.6 pounds/gallon

Bulk density N/A

10. Stability and Reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

Hazardous polymerization None under normal processing.

Conditions to avoid

Keep out of reach of children. Extremes of temperature and direct sunlight. Mixture with or exposure to incompatible materials. **Incompatible materials**

Strong oxidizing agents, Strong acids, Strong bases.

Hazardous decomposition products

Carbon monoxide, Carbon Dioxide (CO2), Aldehydes, Aromatic hydrocarbons, May emit toxic fumes under fire conditions.

Revision Date 20-Apr-2016 PC2032A - KEY PC2032A

11. Toxicological Information

Information on likely routes of exposure

The product has not been tested **Product Information**

Inhalation Remove to fresh air. Harmful by inhalation.

Vapor may cause irritation. Avoid contact with eyes. Severely irritating to eyes. **Eve contact**

Skin contact Avoid contact with skin. Irritating to skin. May cause sensitization by skin contact.

Not an expected route of exposure. Harmful if swallowed. Ingestion

Chemical name	ATEmix (oral)	ATEmix (dermal)	Inhalation LC50
Bisphenol A diglycidyl ether resin	= 11400 mg/kg (Rat)	-	=
25068-38-6			
Proprietary epoxy resin	= 17100 mg/kg (Rat)	-	-
Dibutyltin dilaurate	= 175 mg/kg (Rat) = 45 mg/kg (= 630 mg/kg (Rabbit)	-
77-58-7	Rat)	- 5 ,	

Information on toxicological effects

N/A.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Repeated or prolonged contact may cause skin irritation and dermatitis.

Serious eye damage/eye irritation Irritating to eyes.

Irritation Irritating to eyes and skin.

Sensitization May cause sensitization by skin contact.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity This product does not contain any carcinogens or potential carcinogens as listed by OSHA,

IARC or NTP.

May cause harm to the unborn child. May impair fertility. Reproductive toxicity STOT - single exposure May cause disorder and damage to the. thymus.

Causes damage to organs through prolonged or repeated exposure. thymus. STOT - repeated exposure

Repeated skin contact may lead to irritation and to sensitization, possible with **Chronic Toxicity**

cross-sensitization to other epoxies.

Aspiration hazard N/A

Numerical measures of toxicity - Product Information

4.5% of the mixture consists of ingredient(s) of unknown toxicity Unknown acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

2,703.00 mg/kg ATEmix (oral) ATEmix (dermal) 48,462.00 mg/kg ATEmix (inhalation-dust/mist) 3.85 mg/l

12. Ecological Information

Ecotoxicity

5.8 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemic	al name	Algae/aquatic plants	Fish	Crustacea
Dibutyltin	dilaurate		2: 48 h Oryzias latipes mg/L LC50	
77-	58-7			

Persistence and degradability

N/A

Other adverse effects

N/A

13. Disposal Considerations

Waste treatment methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

Chemical name	California Hazardous Waste Status
Dibutyltin dilaurate 77-58-7	Toxic

14. Transport Information

DOT Not regulated

ICAO (air)

UN/ID no. UN3082

Proper shipping name Environmentally Hazardous Substance Liquid N.O.S. (Bisphenol A epoxy resin)

Hazard Class 9
Packing Group III

<u>IATA</u>

UN/ID no. UN3082

Proper shipping name Environmentally Hazardous substance Liquid N.O.S. (Bisphenol A epoxy resin)

Hazard Class 9
Packing Group III

IMDG

UN/ID no. UN3082

Proper shipping name Environmentally Hazardous Substance Liquid N.O.S. (Bisphenol A epoxy resin)

Hazard Class 9
Packing Group III

Special Provisions IMDG code 2.9.3

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to

IMDG/IMO

15. Regulatory Information

International Inventories

TSCA All components of this product are either exempt or included on the TSCA Inventory in

compliance with the Toxic Substances Control Act.

IECSC All components are listed or exempted.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

The following chemicals may be contained in this product in de minimis amounts not required for listing in section 3. However, these chemicals do appear on some state Right-to-Know (RTK) and/or other hazardous substance lists. Please check your state's listings for more information.

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Glycidyl phenyl ether - 122-60-1	Carcinogen
	Male Reproductive

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations.

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards N/A Flammability N/A Instability N/A Physical and chemical

properties -

HMIS Health hazards 2* Flammability 1 Physical hazards 0 Personal Protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Prepared By Key Polymer Corp Compliance

Issuing Date12-Jan-2015Revision Date20-Apr-2016

Revision Note

N/A

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

Revision Date 20-Apr-2016 PC2032A - KEY PC2032A information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. **End of Safety Data Sheet**